



IX2 AIR

Wireless Thermal Camera for Smart devices

Equipped with a high-sensitivity 256×192 resolution infrared detector, the IX2 AIR can be freely combined or separated with a smartphone according to the scenarios. It supports wireless image transmission and operation. With the supporting App for functions such as real-time analysis and transmission, the device can be widely used in electrical maintenance, equipment inspection, HVAC leak detection, and other fields.



Product Highlights


Wireless Measurement, Unlocking New Scenarios

- Image transmission delay < 300ms.
- With 2 hours of battery life, productivity is always alive.
- The fuselage comes with a back clip and standard threaded holes, which can be matched with various accessories to facilitate users to observe targets at different angles.



Clear Thermal Images, Precise Temperature Measurement

- Built-in 12μm 256×192 infrared detector, featuring low power consumption and small size.
- 40mK professional-grade high thermal sensitivity, capturing smaller temperature differences; wider temperature measurement range of up to 550°C.
- Four image modes + 7 palettes, suitable for temperature observation of different targets and different scenes.




Hard-core Configuration, Easy to Use and Convenient

- IP54 waterproof and dustproof, 2m drop protection, light and slim design that fits your hand.
- Faster Wi-Fi connection with the assistance of Bluetooth; OTA upgrade can be easily completed through the mobile app.
- Professional app that supports full-scenario applications such as real-time analysis and offline analysis of temperature measurement images.



Specifications	IX2 AIR SE	IX2 AIR
Thermal Imaging		
Detector Type	12μm uncooled infrared detector	
Infrared Resolution	256×192	
Spectral Band	7.5~14μm	
NETD	<40mK (25°C,F1.0)	
Frame Rate	25Hz	
Lens Focal Length	3.2mm	
FOV	56°×42°	
IFOV	3.75mrad	
Focus Mode	Fixed focus	
Minimum Imaging Distance	0.3m	
Measurement Range	-20°C~+150°C, +100°C~400°C	-20°C~+150°C, +100°C~550°C
Measurement Accuracy	±2°C or ±2% of readings, whichever is greater.	
Image Display		
Visible Light Camera	/	2 MP
Palettes	7	
Image Mode	Infrared	Infrared, visible, PIP, blending, detail enhancement
Temperature Width Stretch	Auto	
Measurement and Analysis		
App Analysis Function	Central temperature point/Highest temperature point/Lowest temperature point, 1 preset analysis template (support 3 custom points, 3 custom lines, and 3 custom frames)	
System Functions		
Communication Protocol	Wi-Fi, USB, Bluetooth	
Connection	WiFi, Type-C	
Others		
OTA	Support OTA upgrade	
Battery	1050mAh	
Battery Life	About 2h	
Charging Mode	USB Type-C	
Clamp Width	Minimum 131mm/Maximum 172mm	
Tripod Socket	UNC 1/4-20 interface for tripod	
Operating Temperature	-10°C~+50°C	
Operating Humidity	10%~90% (non-condensing)	
Storage Temperature	-20°C~+60°C	
Ingress Protection Rating	IP54	
Shock and Vibration	2G(IEC60068-2-6)、25G(IEC60068-2-29)	
Weight	130g	132g
Authentication	CE/RoHS/DGM/WEEE/ Measure	
Packing List	Data cable×1, complete machine×1, quick start guide×1, packing list×1, quality certificate×1	


Applications




Power Maintenance



Equipment Inspection



HVAC Leak Detection



Circuit Board Repairing

Raythink Technology Co., Ltd.

Company Address: No.5 Wanshoushan Road, Fulaishan Street, Yantai Area of China (Shandong) Pilot Free Trade Zone
 Postal Code: 264000 Official Website: <http://www.raythink-tech.com> Service Email: sales@raythink-tech.com

*The information is for illustrative purposes only. The pictures and technical specifications are subject to change without prior notice. Sample No.: G2024-IX2 AIR-2P001